

MULTISPEC[®] GS (Green Series) Low Odor, Low VOC Multicolor Paint



- ❑ *Tough, long-wearing finish. Superior washability and scuff, mar and stain resistance. Ten year durability under normal use and service*
- ❑ *Attractive multicolored natural appearance with excellent camouflaging properties. Spot repairs blend in invisibly*
- ❑ *Low odor for application in occupied spaces—offices, hospitals, hotels, schools, terminals, major renovations*
- ❑ *Low VOC less than 60 grams per liter. Compliant with Green VOC Standards in all states. Safe and environment friendly*
- ❑ *Easy to apply, maintain and repair. Uniform consistency and repeatable one-step spray application with very controllable HVLP spray equipment*
- ❑ *Tintable with conventional latex tinting systems*

TECHNICAL SUMMARY

Coverage: 125-175 square feet per gallon when sprayed over smooth properly primed surface.

Shelf Life: Use within one year from date of manufacture. Avoid temperature extremes.

Dry Time: Air dry (70° F at 50% humidity). To touch, 1-2 hours. To use or recoat, 24 hours. Standard performance levels typically achieved after seven days.

VOC Content: Maximum 60 grams/liter, 0.5 lbs.per gal. Non-photochemically reactive.

Ingredients: Water (CAS#7732-18-5) Modified Acrylic Polymer (Proprietary-TSRN01390) Titanium Dioxide (CAS#13463-67-7) Cosolvent (Proprietary-TSRN01867) Silicone Dioxide (CAS#112926-00-8)

HMIS Rating: Health 1; Flammability 0; Reactivity 0; Personal Protection I.

ORDERING INFORMATION

Available in gallons (2 per carton).
10 lbs per gallon.

For Information, Call 800.792.9505

For Orders, Call 800.362.6617

Manufactured by Multicolor Specialties, Inc.
www.multicolorpaint.com



MULTISPEC[®]

